



WINDSOR[®] XL



HIGH-PROFILE FLEXOR[™] POLYMER MODIFIED DESIGNER SHINGLES

Distributed from:



Shown in:
Weathered Wood



DISTRIBUTED FROM:
● PORTLAND, OR
● SOUTH GATE, CA
● OKLAHOMA CITY, OK

COLOR AVAILABILITY

Windsor[®] XL

- Midnight Black
- Natural Wood
- Storm Grey
- Weathered Wood



WINDSOR® XL



XL

HIGH-PROFILE DESIGN

Windsor® XL shingles are 20% thicker than Windsor® shingles, with a 17% increase in overall mass.



FLEXOR™ POLYMER MODIFIED ASPHALT

Asphalt technology increases flexibility, granule adhesion, and impact resistance.



PROTECT FROM EXTREME WEATHER

Class 4 impact resistance offers your roof the highest rated protection available.



SCOTCHGARD™ PROTECTOR: HELP PREVENT BLACK STREAKS

Helps maintain the aesthetic appearance of your roof. Includes a 20-year warranty.



RETAIN COLOR GRANULES

Superior granule adhesion provides your roof lasting beauty and protection from damaging solar rays.



SEAL TO ROOF

Specially formulated asphalt sealant holds the shingle in place during high winds.



SUPERIOR SHINGLE STRENGTH

Shingles with Flexor™ polymer modified asphalt are more resistant to tearing and nail pull-out, reducing the risk of shingle blow-off.



FLEXIBLE IN ALL WEATHER

Asphalt technology provides flexibility for application in a wider range of climates and roof styles.




WIND WARRANTIES


110 mph (177 kph) Limited Wind Warranty included. Eligible for a 140 mph (225 kph) Enhanced Wind Warranty when conditions are met.




MIDNIGHT BLACK



NATURAL WOOD



STORM GREY



WEATHERED WOOD



FEATURING

- Limited Lifetime Shingle Warranty
- 15-year Right Start™ Warranty

TEST COMPLIANCE

- ASTM D7158 Class H
- ASTM D3161 Class F
- ASTM E108 Class A Fire Rating
- CSA A123.5
- ASTM D3462
- ASTM D3018 Type I
- UL 2218 Class 4



GREENCIRCLE CERTIFIED MANUFACTURING FACILITY

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Shingle colors not available in all regions. Limited warranties carry terms and conditions. Please contact your local Malarkey representative for color availability and further information. See Malarkey's Shingle and Accessory Warranty for details.

* For complete Limited Lifetime Warranty details, reference Malarkey's Shingle and Accessory Warranty. For Windsor® XL shingles, use of Windsor® Starter shingles are required for installation, and to receive Limited Lifetime Warranty protection.

* Malarkey shingles featuring Scotchgard™ Protector must be installed with EZ-Ridge™ (8", 10") or RidgeFlex™ (10", 12") hip and ridge products, which feature Scotchgard™ Protector, to receive Malarkey's full 20-year Algae Resistant Shingle warranty. The Alaskan™ featuring Scotchgard™ Protector can be substituted as hip and ridge shingles, in conjunction with Malarkey shingles featuring Scotchgard™ Protector, to receive the full Malarkey 20-year Algae Resistant Shingle warranty. Scotchgard and the Scotchgard logo, including the 3M logo, are all trademarks of 3M.

** Shingles come with a 110 mph (177 kph) Limited Wind Warranty. Eligible for a 140 mph (225 kph) Enhanced Wind Warranty when Smart Start™ starter shingles are installed, shingles are 9-nailed, and either EZ-Ridge™ (8", 10") or RidgeFlex™ (10", 12") hip and ridge shingles are used. Some contractors adapt roofing shingles to use as hip and ridge shingles. Use of The Alaskan™ as a hip and ridge shingle will apply towards the Enhanced Wind Warranty. Dura-Seal™ shingles used for hip and ridge will not qualify toward an Enhanced Wind Warranty. Malarkey performance-driven underlayments – Arctic Seal®, Right Start™ UDL, or SecureStart™ – are recommended for added system protection. This version supersedes all previous versions. Rev. 10/16



Malarkey
Roofing Products®
Defining Excellence.™

P.O. BOX 17217, PORTLAND, OR 97217
503.283.1191 | 800.545.1191 | FAX: 503.289.7644

WWW.MALARKEYROOFING.COM